

L9CH Series - 19" LCD Monitor

- Product Specifications -

Configuration		L9CH
LCD Display Area		19.0" TFT active matrix panel
Display Area (HxV)		14.8"x 11.9" (376.32x301.056mm)
Pixel Pitch (HxV)		0.294x0.294mm
Maximum Resolution		SXGA 1280x1024
Contrast Ratio		600:1
Brightness		250 cd/m2
Response Time		25 ms
Display Color		16M
Viewing Angle	L/R	170° (+85°~-85°)
	U/D	170° (+85°~-85°)
PC Interface	Video	RGB analog 0.7Vp-p
	Sync.	TTL positive or negative
Display Mode		VGA 720x400 (70 Hz)
		VGA 640x480 (60/70/72/75 Hz)
		SVGA 800x600 (56/60/72/75 Hz)
		XGA 1024x768 (60/70/75 Hz)
		SXGA 1280x1024 (60/75 Hz)
Signal Connector	Analog	D-sub 15 pin
	Digital (optional)	DVI 24 pin (optional)
Front Control		Power on/off with LED, Menu, Select, Adjustment (+,-)
Plug & Play		DDC 1/2B compatible
Speakers (Internal)		2W / per channel driver
Power		Input AC 100~240V, 50~60Hz; Output DC 12V / 4A
Operating Conditions	Temperature	41°F~95°F (5°C~35°C)
	Humidity	20%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-4°F~140°F (-20°C~60°C)
	Humidity	10%-90% (no condensation)
Dimensions (HxWxD)		17.7"x17.2"x7.7" (450x 437x195mm)
Weight (net)		13.7lbs. (6.2Kgs)
Optional Module		Analog, Dual inputs, Adjustable arm
Certification		C-UL, FCC, CE, TUV/GS, BSMI, EPA, NUTEK, TCO

Specifications are subject to change without notice.



KOGi

20532 Crescent Bay Drive, Suite 104
 Lake Forest, CA 92630
 Tel: (949) 586-3338
 Fax: (949) 586-3398